

TECHNICAL DATA SHEET

RP EnviroCote Ceiling

Description	RP EnviroCote Ceiling is a premium ceiling white paint formulated for interior use. This environmentally friendly low V.O.C. (Volatile Organic Compound) formulation is a waterborne ceiling paint, specifically designed for the professional painter. RP EnviroCote Ceiling does not contain any crystalline silica which is harmful to human health and can lead to Silicosis. Formulated from high grade components, this emulsion based product provides maximum adhesion to most surfaces and dries to an ultra-flat finish with excellent opacity.
Features	<ul style="list-style-type: none"> • Safe/low odour • Low spatter • Easy touch up • High Flow • Excellent Workability • High opacity
Benefits	<ul style="list-style-type: none"> • Quick application • Low VOC • Great coverage and hiding capacity
Uses	<ul style="list-style-type: none"> • RP EnviroCote Ceiling is for use on ceilings only
Colour and Gloss	<ul style="list-style-type: none"> • RP EnviroCote Ceiling can be tinted to off-white shades or hues to create a continuity or "flow" between wall and ceiling colours. However it has not been formulated to exactly match a Revolution white base.
Sheen Level	<ul style="list-style-type: none"> • Flat
Typical Data at 25°C and 50% Relative Humidity	
Thinning	<ul style="list-style-type: none"> • 5% Water
Coverage Rate	<ul style="list-style-type: none"> • Coverage rates may vary according to substrate and preparation. RP EnviroCote Ceiling is usually applied at the rate of approximately 16m²/ltr/coat.
Drying Time	<ul style="list-style-type: none"> • 2 hours
Touch Dry	<ul style="list-style-type: none"> • 30 minutes
Dry to Recoat	<ul style="list-style-type: none"> • 2 hours
Usual No Coats	<ul style="list-style-type: none"> • 02
Packaging Sizes	<ul style="list-style-type: none"> • 8 Ltr & 18 Ltr
Clean Up	<ul style="list-style-type: none"> • Water
Substrate Conditions	<ul style="list-style-type: none"> • Ensure the surface is free from loose material, clean, dry and free from oil and grease. Sand any non-porous surfaces such as glossy painted areas. Patch and fill holes and cracks with suitable plaster patching compound and sand back to give an even finish before painting. Do not sand the paper surface of plasterboard. • Clean any mould, mildew or fungi. RP EnviroCote Ceiling does not support the growth of mould, mildew or fungi. • For previously painted: A sealer is not normally required. • Cement and cement sheet: If required apply one coat RP EnviroCote Primer then two coats of RP EnviroCote Ceiling • Timber and hardboard: Apply one coat of RP EnviroCote Primer then two coats of RP EnviroCote Ceiling



Revolution Paint



	<ul style="list-style-type: none"> Timbers that are rich in tannins: A stain resistant primer should be used
Flooring Installation	<ul style="list-style-type: none"> N/A
Mixing	<ul style="list-style-type: none"> N/A
Application	<ul style="list-style-type: none"> If using multiple pails, contents must be boxed together to ensure colour consistency Be sure to keep a wet edge with this product and plan your work to suit the product and weather conditions. For airless spray use 0.013 - 0.017inch spray tips and adjust the flow rate and fan width to minimize water required to thin Can be thinned up to 5% volume with water
Safety Data	<ul style="list-style-type: none"> Refer to RP EnviroCote Ceiling SDS
Precautions and Limitations	<ul style="list-style-type: none"> RP EnviroCote Ceiling should not be applied in temperatures below 5°C or above 40°C RP EnviroCote Ceiling is not suitable for areas of continual damp or areas submerged in water Not for use over unsealed hardwood
Transport and Storage	<ul style="list-style-type: none"> Store in a cool dark place Keep pail sealed Do not stack more than 3 pails high Do not double stack pallets Top load only
Disposal	<ul style="list-style-type: none"> Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal Product must not be allowed to run into drains or open bodies of water Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
Recommendation for Application	<ul style="list-style-type: none"> UNi-PRO is recommended to use for the best quality

*** Due to our policy of continuing product improvement Revolution Paint reserves the right to modify these specifications without further notice.

