

TECHNICAL DATA SHEET

RP Interior Premium Putty - White

Pack size	<ul style="list-style-type: none"> 40 kg
Product Code	<ul style="list-style-type: none"> 50511
Color Range	<ul style="list-style-type: none"> White
Usage	<ul style="list-style-type: none"> RP Interior Premium Putty - White is a treatment material for patching-up of uneven concrete or plastering surface. The product is high quality, easy in application and designed for both interior and exterior use
Area of Application	<ul style="list-style-type: none"> Concrete, mortar, plaster, precast concrete, hard and soft boards
Characteristic	<ul style="list-style-type: none"> One-pack type for easy handling Maximum adhesion to the substrate and cohesion strength Hair-line crack resistance, impact and scrub resistance. Forms a hard surface after curing without any shrinkage cracks. Strengthens weak surfaces of substrate and enhance performance of finish coats. Excellent durability and weather resistance for finishing coats Excellent sanding properties, minimum powder release with little scratch mark appear on the finish
Composition	<ul style="list-style-type: none"> Binder, cement, sand & Additives
DRYING TIMES	Single coat at standard thickness 1mm.
Surface Dry	<ul style="list-style-type: none"> 30 – 60 minutes (Dependent on temperature and humidity).
Recoat	<ul style="list-style-type: none"> 1 – 2 hours after the first coat
Sanding	<ul style="list-style-type: none"> 1 day after application
Hard Dry	<ul style="list-style-type: none"> 1 day at 300C
Paint apply	<ul style="list-style-type: none"> Paints will be applied after
Theoretical Coverage	<ul style="list-style-type: none"> 1 - 1,2 m2/ Kg.
Application Tool	<ul style="list-style-type: none"> Steel trowel to achieve high effectiveness.
MIXING INSTRUCTION	
Mixing Ratio	<ul style="list-style-type: none"> 1 part of water to 2.5 parts of material by weight. Let water into tin first, then pouring the powder slowly. Use a mixer if available or adequate mixing equipment to mix until having homogenous paste which is then ready for use.
Surface Preparation	<ul style="list-style-type: none"> Surface must be dry and clean from dirt, dust, oil, grease and foreign matters. All large cracks on the surface of wall or ceiling must be filled prior to application. Do not filling RP Interior Premium Putty – White if the temperature of surface for application should not be under 400°C. In case

	of the dry wall and aborted surface must be wet and reducing the surface temperature by water by water spray method before filing.
Pot life	<ul style="list-style-type: none"> • 3 hours
Safety, Health and Environmental Information	<ul style="list-style-type: none"> • Irritating to respiratory system and skin. • Avoid contact with eyes. • Risk of serious damage to eyes. • In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. • Wear eye/face protection. • Contents: CEMENT WITH > 2PPM CHROMIUM VI. May produce allergic reaction. • Keep out of reach of children. • If swallow, seek medical advice immediately and show this container or label. • Wear suitable gloves. • Dispose of any putty waste in accordance with the appropriate Environment Quality Regulations
Recommendation for Application	<ul style="list-style-type: none"> • UNi-PRO is recommended to use for the best quality

**** Due to our policy of continuing product improvement Revolution Paint reserves the right to modify these specifications without further notice.*

