

## TECHNICAL DATA SHEET

### RP Exterior Premium Skimcoat

<b>Product name</b>	<ul style="list-style-type: none"> <li>RP Exterior Premium Skimcoat</li> </ul>
<b>Product code</b>	<ul style="list-style-type: none"> <li>50513</li> </ul>
<b>Pack size</b>	<ul style="list-style-type: none"> <li>40kg</li> </ul>
<b>Colour range</b>	<ul style="list-style-type: none"> <li>White/Grey</li> </ul>
<b>Usage</b>	<ul style="list-style-type: none"> <li>RP Exterior Premium Skimcoat is a treatment material for patching-up of uneven concrete or plastering surface. The product is high quality, easy in application and designed for both interior and exterior use</li> </ul>
<b>Area of application</b>	<ul style="list-style-type: none"> <li>Concrete, mortar, plaster, precast concrete, hard and soft boards</li> </ul>
<b>Characteristics</b>	<ul style="list-style-type: none"> <li>One-pack type for easy handling</li> <li>Maximum adhesion to the substrate and cohesion strength</li> <li>Hair-line crack resistance, impact and scrub resistance.</li> <li>Forms a hard surface after curing without any shrinkage cracks.</li> <li>Strengthens weak surfaces of substrate and enhance performance of finish coats.</li> <li>Excellent durability and weather resistance for finishing coats</li> <li>Excellent sanding properties, minimum powder release with little scratch mark appear on the finish</li> </ul>
<b>Composition</b>	<ul style="list-style-type: none"> <li>Binder, cement, sand &amp; Additives</li> </ul>
<b>Drying time</b>	<ul style="list-style-type: none"> <li>Single coat at standard thickness 1mm</li> </ul>
<b>Surface Dry</b>	<ul style="list-style-type: none"> <li>30 – 60 minutes (Depending on temperature and humidity)</li> </ul>
<b>Recoat</b>	<ul style="list-style-type: none"> <li>1 – 2 hours after the first coat</li> </ul>
<b>Sanding</b>	<ul style="list-style-type: none"> <li>1 day after application</li> </ul>
<b>Hard dry</b>	<ul style="list-style-type: none"> <li>1 day at 30°C</li> </ul>
<b>Paint apply</b>	<ul style="list-style-type: none"> <li>Paints will be applied after</li> </ul>
<b>Theoretical coverage</b>	<ul style="list-style-type: none"> <li>1 – 1.2m<sup>2</sup>/kg</li> </ul>
<b>Application tools</b>	<ul style="list-style-type: none"> <li>Steel trowel to achieve high effectiveness</li> <li>1 part of water to 2.5 parts of material by weight</li> </ul>
<b>MIXING INSTRUCTION</b>	
<b>Mixing ratio</b>	<ul style="list-style-type: none"> <li>Let water into tin first, then pouring the powder slowly. Use a mixer if available or adequate mixing equipment to mix until having omogenous paste which is then ready for use</li> </ul>
<b>SURFACE PREPARATION</b>	<ul style="list-style-type: none"> <li>Surface must be dry and clean from dirt, dust, oil, grease and foreign matters. All large cracks on the surface of wall or ceiling must be filled prior to application. Do not filling RP Exterior Premium Skimcoat if the temperature of surface for application should not be under 40°C. In case of the dry wall and absorptive surface must be wet and reducing the surface temperature by water by water spray method before filing</li> </ul>
<b>Pot life</b>	<ul style="list-style-type: none"> <li>3 hours</li> </ul>

## SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

- Irritating to respiratory system and skin.
- Avoid contact with eyes.
- Risk of serious damage to eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Wear eye/face protection.
- Contents: cement with > 2ppm chromium VI. May produce allergic reaction.
- Keep out of reach of children.
- If swallow, seek medical advice immediately and show this container or label.
- Wear suitable gloves.
- Dispose of any putty waste in accordance with the appropriate Environment Quality Regulations

All above information is provided with high reliability but without implied warranties as the quality of the finish paint film depends on application conditions.

## Recommendation for Application

- Use UNi-Pro products for the best quality

\*\*\* Due to our policy of continuing product improvement Revolution Paint reserves the right to modify these specifications without further notice.

